

REVISION DATA				
SYM	ECN	DESCRIPTION	DATE	APPROVED

A

B

C

D

E

F

A



B

C

D

E

F



面板开孔图

Panel cut

技术参数:
插芯:
插针数: 216+PE
额定电流: 10A
工作电压: 250V
额定脉冲电压: 4KV
污染等级: 3
依据UL/CSA的额定电压: 600V
绝缘阻抗: $\geq 10^{10} \Omega$
材料: 聚碳酸酯
温度范围: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
依据UL94的阻燃等级: V0
可插拔次数: ≥ 500

Specifications:
Inserts:
Number of contacts: 216+PE
Rated current: 10A
Rated voltage: 250V
Rated impulse voltage: 4KV
Pollution degree: 3
Rated voltage acc.to UL/CSA:600V
Insulation resistance: $\geq 10^{10} \Omega$
Material: Polycarbonate
Limiting temperatures: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
Flammability acc.to(UL94): V0
Mechanical working life -mating cycles: ≥ 500

插针:
接线方式: 冷压连接
材料: 铜合金
表面处理: 镀银 镀金
接触电阻: $\leq 3\text{m}\Omega$
线径范围: 0.14~2.5mm² (AWG26-14)

Contacts:
Terminal: Crimp terminal
Material: Brass
Surfac: hard-silver plated/Gold plated
Contact resistance: $\leq 3\text{m}\Omega$
Crimp terminal
Wire gauge--mm²: 0.14~2.5mm²
Wire gauge--AWG: 26-14

Tolerance		SIGNATURE	DATE	Units	mm	 宁波欧科瑞连接器有限公司 NINGBO OUKERUI CONNECTOR CO.,LTD.		
0~ ≤ 20	± 0.15	DRAW		Size	A4			
20~ ≤ 50	± 0.25	DESIGN		Scale		PART NAME: HZW-HDD-216-M		
50~ ≤ 80	± 0.35	CHECK		Sheet		Drawing NO.		REV
80~ ≤ 120	± 0.50	APPROVE		Proj.		Material		A