



**技术参数:**

材料: 压铸铝  
 表面处理: 粉末喷涂  
 颜色: RAL9005黑色  
 温度范围: -40°C~+125°C  
 防护等级: IP68 (联锁状态)  
 密封元件: NBR  
 出线方向: 侧出线  
 螺纹尺寸: M20/M25/M32/M40/PG16/PG21/PG29

**Specifications:**

Material: aluminium die-cast  
 Surface: powder-coated  
 Color: BLACK (RAL 9005)  
 Limiting temperatures: -40°C~+125°C  
 Degree of protection : IP68  
 Hoods/Housings sealing: NBR  
 Cable entry: side exit line  
 Thread size: M20/M25/M32/M40/PG16/PG21/PG29

**REVISION DATA**

| SYM | ECN | DESCRIPTION | DATE | APPROVED |
|-----|-----|-------------|------|----------|
|     |     |             |      |          |
|     |     |             |      |          |



宁波欧科瑞连接器有限公司  
 NINGBO OUKERUI CONNECTOR CO., LTD.

| Tolerance     | SIGNATURE | DATE | Units | mm |
|---------------|-----------|------|-------|----|
| 0~≤20 ±0.15   | DRAW      |      | Size  | A4 |
| 20~≤50 ±0.25  | DESIGN    |      | Scale |    |
| 50~≤80 ±0.35  | CHECK     |      | Sheet |    |
| 80~≤120 ±0.50 | APPROVE   |      | Proj. |    |

| PART NAME:            | REV |
|-----------------------|-----|
| HZW-HP24B-SKH-2S-M/PG |     |
| Drawing NO.           |     |
| Material              | A   |