



技术参数:

材料: 压铸铝

表面处理: 粉末喷涂

颜色: RAL9005黑色

温度范围: -40℃~+125℃

防护等级: IP68 (联锁状态)

密封元件: NBR

出线方向: 侧出线

螺纹尺寸: M20/M25/M32/M40/PG16/PG21/PG29

Specifications:

Material: aluminium die-cast

Surface: powder-coated

Color: BLACK (RAL 9005)

Limiting temperatures: -40℃~+125℃

Degree of protection : IP68

Hoods/Housings sealing: NBR

Cable entry: side exit line

Thread size:M20/M25/M32/M40/PG16/PG21/PG29

REVISION DATA			
SYM	ECN	DESCRIPTION	DATE

		宁波欧科瑞连接器有限公司 NINGBO OUKERU CONNECTOR CO., LTD.	
		PART NAME: HZW-HP168-SKH-2S-M/PG	REV
Tolerance		Drawing NO.	
0~≤20 ±0.15	DRAW	Sheet	
20~≤50 ±0.25	DESIGN	Proj.	
50~≤80 ±0.35	CHECK	Material	
80~≤120 ±0.50	APPROVE	Material	

Tolerance	SIGNATURE	DATE	Units	mm
0~≤20 ±0.15	DRAW		Size	A4
20~≤50 ±0.25	DESIGN		Scale	
50~≤80 ±0.35	CHECK		Sheet	
80~≤120 ±0.50	APPROVE		Proj.	